



# Safety Data Sheet

## Oil Coated Fusite

Revision date:  
May 20, 2015

### 1. Identification

---

**Product Name:** Oil Coated Fusite  
**Synonyms:** None  
**Recommended Uses:** Water treatment, steel flux, caustic agent, pH adjustment, acid gas absorption, construction  
**Manufacturer:** Carmeuse Lime & Stone

US Office  
11 Stanwix Street, 21<sup>st</sup> Floor  
Pittsburgh, PA 15222  
Phone: (412) 995-5500  
Fax: (412) 995-5594

Canadian Office  
PO Box 190  
Ingersoll, ON N5C 3K5  
Phone: (519) 423-6283  
Fax: (519) 423-6545

**Emergency Contact:** Infotrac: (800) 535-5053 (24 hrs a day, 7 days a week)

### 2. Hazards Identification

---

<b>GHS classification</b>	<b>Physical Hazards</b>	Combustible Liquid ( <i>refers to coating on pebble</i> )	Category 4
	<b>Health Hazards</b>	Skin Irritation	Category 2
<b>GHS Label Elements:</b>		Eye Damage	Category 1
		Carcinogenicity	Category 1A
		Specific Target Organ Toxicity – Single Exposure	Category 3
		Specific Target Organ Toxicity – Repeated Exposure	Category 1
	<b>Signal Word:</b>	Danger	
	<b>Hazard Statements:</b>	Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause cancer through inhalation Causes damage to lungs through prolonged or repeated exposure by inhalation. Combustible liquid ( <i>refers to coating on pebbles</i> )	
	<b>Precautionary Statements:</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in well-ventilated area Wear protective gloves, clothing and eye protection Do not use water on material spills. Keep away from flames and hot surfaces Store in a well-ventilated place. Keep cool	

# Oil Coated Fusite

**Pictograms:**



### 3. Composition

<u>Chemical name</u>	<u>% by weight</u>	<u>CAS#</u>
Calcium oxide	> 55	1305-788
Magnesium oxide	< 34	1309-48-4
Iron Oxide	< 12	1309-37-1
Clarified Petroleum oils	< 2	64741-62-4
Silica-crystalline quartz	0.1 - 2	14808-60-7

### 4. First Aid Measures

<b>Eyes:</b>	Immediately flush eyes with generous amounts of water for at least 15 minutes. Pull back the eyelid to ensure that all lime dust has been washed out. Seek medical attention immediately. Do not rub eyes.
<b>Skin:</b>	Wash exposed area with large amounts of water. Seek medical attention immediately.
<b>Ingestion:</b>	Do not induce vomiting. Seek medical attention immediately. Never give anything by mouth unless instructed to do so by medical personnel.
<b>Inhalation:</b>	Move victim to fresh air. Seek medical attention if necessary. If breathing has stopped, give artificial respiration
<b>Most Important Symptoms:</b>	Irritation of skin, eyes, gastrointestinal tract or respiratory tract.
<b>Immediate medical attention / special treatment?</b>	See first aid information above. Note to Physicians: Provide general supportive measures and treat symptomatically.

### 5. Fire Fighting Measures

<b>Suitable (and unsuitable) fire extinguishing media:</b>	Use dry chemical fire extinguisher. Do not use water or halogenated compounds, except that large amounts of water may be used to deluge small quantities of this product.
<b>Specific hazards arising from the product</b>	Inhalation, skin or eye contact, can result in serious injury. The oil coating is combustible. This product reacts with water, and can release heat sufficient to ignite combustible materials. This product is not considered to be an explosion hazard, although reaction with water or other incompatible materials may rupture containers. When this product is wet, it can be very slippery and can result in a slip hazard. Hazardous Combustion Products: None.



Safety Data Sheet  
**Oil Coated Fusite**

Revision date:  
 May 20, 2015

**Special protective equipment and precautions for fire fighters**

Wear full fire-fighting turn-out gear (full Bunker gear), and respiratory protection (SCBA) to prevent inhalation, skin or eye contact.

**6. Accidental Release Measures**

**Personal precautions, protective equipment, emergency procedures:**

Avoid inhalation, eye and skin contact. Avoid generating airborne dust. Wear appropriate protective clothing as described in section 8.

**Methods and materials for containment and clean up:**

Utilize cleanup methods that minimize generating dust: vacuum. Avoid dry sweeping. Do not use water on large spills, as this product reacts with water and releases heat. Residue on surfaces may be removed with copious amount of water or vinegar.

**7. Handling & Storage**

**Safe Handling:** Avoid inhalation, skin and eye contact. Avoid generating airborne dust. An eye wash station should be readily available when this product is handled.

**Safe Storage:** Keep in tightly closed containers. Protect containers from physical damage. Store in a cool, dry, and well-ventilated location. Do not store near incompatible materials (see Section 10 below). Keep away from moisture. Long-term storage in aluminum containers is not recommended, as calcium oxide may corrode aluminum over long periods of time

**8. Exposure Controls/Personal Protection**

**Occupational Exposure Limits**

	OSHA PEL (mg/m <sup>3</sup> )	ACGIH TLV (mg/m <sup>3</sup> )	Ont. Reg. 833 TWAEV (mg/m <sup>3</sup> )
Calcium oxide	5	2	2
Magnesium oxide	15	10	10
Iron Oxide*	5 (fume) 15 (total) 5 (respirable)	5	5 (respirable)
Clarified Petroleum oils silica - crystalline quartz	- 30 / (% silica +2) (total) 10 / (% silica +2) (respirable)	- 0.025 (respirable)	- 0.1

\*PELs for Particulates Not Otherwise Classified

**Engineering Controls:** Use with adequate general or local exhaust ventilation and to maintain exposure below occupational exposure limits.

**Individual Protection Measures (Personal Protective Equipment):**

<b>Specific Eye / Face Protection:</b>	Safety glasses with side shields. In windy conditions, or if work activity generates elevated airborne dust levels, dust proof or chemical goggles are recommended. Contact lenses should not be worn.
<b>Specific Skin Protection:</b>	When there is a risk of skin contact, wear appropriate clothing and gloves to prevent contact.
<b>Specific Respiratory Protection:</b>	If exposure limits are exceeded, an approved particulate respirator, or supplied air respirator, appropriate for the airborne concentrations, should be used. Selection and use of the respiratory protective equipment must be in accordance with applicable regulations and good industrial hygiene practices.
<b>Other:</b>	An emergency eye wash fountain and shower are recommended.

**9. Physical & Chemical Properties**

---

<b>Appearance:</b>	White or grayish white material
<b>Odor:</b>	Odorless
<b>Odor threshold:</b>	Not Applicable
<b>pH at 25 degrees C:</b>	12.45
<b>Melting Point:</b>	4658 °F (2570 °C)
<b>Boiling Point and range:</b>	5162 °F (2850 °C)
<b>Flash Point:</b>	140 °F min. (oil coating)
<b>Evaporation Rate:</b>	Not Applicable
<b>Flammability:</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	Not Applicable
<b>Vapor pressure/density:</b>	Non Volatile
<b>Relative density:</b>	2.0-2.8
<b>Solubility:</b>	Negligible in water but reacts with water to produce Ca(OH) <sub>2</sub> and heat Soluble in acids, glycerin, and sugar solutions
<b>Partition coefficient: n-octanol/water</b>	Not applicable
<b>Auto-ignition temperature:</b>	Not Available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not Applicable

## 10. Stability & Reactivity

---

<b>Reactivity:</b>	Reacts with water to form calcium hydroxide and magnesium hydroxide, releasing heat. Reacts with acids to form calcium salts, releasing heat. Reacts with carbon dioxide in air to form calcium carbonate. See also Incompatibility below.
<b>Chemical stability:</b>	Stable under normal storage and handling conditions.
<b>Possibility of Hazardous Reactions:</b>	See "reactivity" above.
<b>Conditions to avoid:</b>	Vicinity of incompatible materials.
<b>Incompatibility:</b>	This product should not be mixed or stored with the following materials, due to the potential for violent reaction and release of heat: <ul style="list-style-type: none"><li>• water (unless in a controlled process)</li><li>• acids</li><li>• reactive fluoridated compounds</li><li>• reactive brominated compounds</li><li>• reactive powdered metals</li><li>• reactive phosphorous compounds</li><li>• aluminum powder</li><li>• organic acid anhydrides</li><li>• nitro-organic compounds</li><li>• interhalogenated compounds</li></ul>
<b>Hazardous decomposition products:</b>	None

## 11. Toxicological Information

---

### Likely routes of exposure & symptoms:

<b>Eyes:</b>	Contact can cause severe irritation or burning of eyes, including permanent damage.
<b>Skin:</b>	Contact can cause severe irritation or burning of skin, especially in the presence of moisture.
<b>Ingestion:</b>	This product can cause severe irritation or burning of gastrointestinal tract if swallowed.
<b>Inhalation:</b>	This product can cause severe irritation of the respiratory system.

# Oil Coated Fusite

Revision date:  
May 20, 2015

<b>Chronic health effects:</b>	This product contains trace amounts of crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica can cause silicosis, a serious lung disease.
<b>Respiratory or skin sensitization:</b>	This material is not known to cause sensitization
<b>Germ cell mutagenicity:</b>	No data available.
<b>Carcinogenicity:</b>	This product is not listed as carcinogenic by OSHA, IARC, NTP, ACGIH, or the EU Directives. This product may contain trace amounts of crystalline silica quartz which is listed by IARC as "Carcinogenic to Humans" (Group 1) and "Known to be a Human Carcinogen" by NTP.
<b>Reproductive toxicity:</b>	No Data Available.
<b>Numerical Measures of Toxicity</b>	Crystalline Silica: Oral Rate LD <sub>50</sub> > 22,500 mg/kg

## 12. Ecological Information

---

Because of the elevated pH of this product, it might be expected to produce some ecotoxicity upon exposure to certain aquatic organisms and aquatic systems in high concentrations  
This material shows no bioaccumulation effect or food chain concentration toxicity.

## 13. Disposal Considerations

---

Dispose of contents in accordance with federal, state, provincial and local regulations.

## 14. Transport Information

---

<b>UN Number</b>	UN1910
<b>UN Proper shipping name</b>	Calcium Oxide
<b>Transport Hazard class(es)</b>	When transported by air only: Hazard Class 8-Corrosive
<b>Packing group</b>	When transported by air only: Packing Group III
<b>Environmental hazards</b>	This material is alkaline and if released into water or moist soil will cause an increase in pH
<b>Transport in bulk (according to Annex II of MARPOL 73/79 and the IBC Code):</b>	

**Special precautions  
 which a user needs to  
 be aware of**

When being transported by air, quicklime is classified in the Department of Transportation (DOT) regulations as a hazardous material. (49 CFR 172.101). For aircraft transport only, Calcium Oxide is classified as Hazard Class 8-Corrosive, UN1910, Packing Group III. For passenger aircraft, the maximum net quantity allowed per container is 25 kg. For cargo aircraft, the maximum net quantity allowed per container is 100 kg. For quantities greater than 25 kg up to and including 100 kg, the container shall be labeled with CARGO AIRCRAFT ONLY. Because express carriers (i.e., Federal Express, Airborne Express, and United Parcel Service) ship by air, quicklime presented to these carriers for shipment must be packaged, marked, and labeled in accordance with IATA requirements, and must be accompanied by the appropriate shipping documentation. Only personnel trained and certified under applicable DOT Hazardous Materials Regulations (contained in Title 49 of the Code of Federal Regulations) may prepare any quicklime product for air transport. Quicklime is not classified as a hazardous material by DOT when transported by means other than by air.

**15. Regulatory Information**

<b>CERCLA Hazardous Substances</b>	Not listed
<b>SARA Toxic Chemical (40 CFR 372.65)</b>	Not listed
<b>SARA Section 302 Extremely Hazardous Substances (40 CFR 355)</b>	Not listed
<b>SARA 311/312</b>	Not listed
<b>SARA Section 313 Toxic Chemicals reporting requirements</b>	None
<b>Threshold planning quantity (TPQ)</b>	Not listed
<b>RCRA Hazardous Waste Classification (40 CFR 261)</b>	Not Classified
<b>EPA Toxic Substances Control Act (TSCA) Status</b>	All of the components of this product are listed on the TSCA
<b>California Proposition 65</b>	Airborne crystalline silica particulates of respirable size are known to the State of California to cause cancer.
<b>NFPA ratings</b>	Health: 3 Fire: 2* Reactivity: 0 $\Psi$
<b>HMIS Ratings</b>	Health: 3 Fire: 2* Reactivity: 1 Personal protection: E *2 rating is due to oil component of material
<b>OSHA Specifically regulated substance (29 CFR 1910)</b>	Not listed
<b>OSHA Air contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A)</b>	Listed
<b>MSHA</b>	Not listed
<b>Canada DSL</b>	Listed
<b>Canadian WHMIS Classification</b>	D2A, Materials Causing other toxic effects. E, Corrosive Material B, Combustible Material ( <i>oil coating</i> )





Safety Data Sheet  
**Oil Coated Fusite**

Revision date:  
May 20, 2015

**Canada CPR** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation of a Canada and this SDS contains all the required information.

**16. Other Information**

---

**List of GHS** H227: Combustible liquid (*coating on pebbles*)  
**Hazard** H315: Causes skin irritation  
**Statements:** H318: Causes serious eye damage  
H335: May cause respiratory irritation.  
H350: May cause cancer through inhalation  
H372: Causes damage to lungs through prolonged or repeated exposure by inhalation.

**List of GHS** P201: Obtain special instructions before use.  
**Precautionary** P202: Do not handle until all safety precautions have been read and understood.  
**Statements:** P210: Keep away from flames and hot surfaces  
P233: Keep container tightly closed  
P260: Do not breathe dust.  
P264: Wash thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in well-ventilated area  
P280: Wear protective gloves, clothing and eye protection  
P403+P235: Store in a well-ventilated place. Keep cool

**Abbreviations**

CERCLA	Comprehensive Environmental Response, Compensation and Liability Act	RCRA	Resource Conservation and Recovery Act
SARA	Superfund Amendments and Reauthorization Act	IARC	International Agency for Research on Cancer
NTP	National Toxicology Program		

The information contained herein is believed to be accurate and reliable as of the date hereof. However, Carmeuse makes no representation, warranty or guarantee as to results or as to the information's accuracy, reliability or completeness. Carmeuse has no liability for any loss or damage that may result from use of the information. Each user is responsible to review this information, satisfy itself as to the information's suitability and completeness, and circulate the information to its employees, customers and other appropriate third parties.